



0800 / 12 24 100*

*Toll-free calls throughout Germany



COMPETENT. FAST. RELIABLE

ACR-3-WV-40 to 125 – Technical Specifications – 3-Way Mixing Valve



Optionally accessories

Cold Water
TubesExt. Pump
ModuleHeat
Exchanger

Different requirements and applications can be provided on request!

Technical description:

Control valve in three-way design with actuator, control cabinet and connections mounted on base frame.

Extensive accessories are available as options.

Technical specifications:

Valve size	DN	40	65	80	100	125
*Water connections	Storz	C	B	B	A	125
Nominal pressure	PN	16	16	16	16	16
Set pressure	bar	2,6	3,2	2,7	1,9	9,5
KVS-value	m ³ /h	25	63	100	160	250
Voltage	V/Hz/Ph	230/50/1	230/50/1	230/50/1	230/50/1	230/50/1
Electrical connection	Schuko Socket	230V	230V	230V	230V	230V
** Fuse protection	A	16	16	16	16	16
** Cable recommendation	mm ²	2,5	2,5	2,5	2,5	2,5
Drive	V	0-10	0-10	0-10	0-10	0-10
Regulating time	Seconds	108	79	130	79	132
Dimensions (l x w x h)	mm	420x420x680	490x480x980	600x700x1370	710x790x1500	700x800x1820
Transport weight	kg	35	35	135	182	230

* Connections individually configurable on request

** On-Site power installation should be entrusted to an electrical specialist.