

COMPETENT, FAST, RELIABLE

# ACR-AH-50 – Technical Specifications – Rental Close Control Air-Conditioning Unit



### Ouick overview

Variable Filter Condensate Speed Control Chamber Drain





## Optionally accessories

Chiller

Heating Unit Water Tubes Electrical Cables Air Transport











Different requirements and applications can be provided on request!

### **Technical specifications:**

Cooling capacity	kW	50
Max.air flow volume	m³ / h	4500
Cold water temperatures	°C	6/12
Air inlet	°C / r.F.	32°C / 40% r.F.
Air outlet	°C	13°C
Heating capacity	kW	97
Hot water temperatures	°C	70/50
Water connections	Storz	С
Filter class	-	M5
External static pressure	Pa	300
Total static pressure	Pa	537
* Voltage / Electrical Connection	V/Hz/Ph	230/50/1 (Socket)
Operating current	Α	8
Sound power	dB (A)	80
Dimensions (I x w x h)	mm	1380 x 780 x 2230
Weight	kg	350

<sup>\*</sup> On-Site power installation should be entrusted to an electrical specialist.

## **Technical description:**

4,500 m³ / h ventilation unit with EC fan, infinitely variable speed regulation and pressure up to 500 Pa. Particularly suitable for cooling storage rooms, event air conditioning, machine cooling, server rooms and production areas. Can also be used for heating warehouses, construction heating, etc., in conjunction with a mobile heating unit. Air distribution by means of air outlet box in 4 directions or with flexible 525 mm air hoses. Extensive accessories are available as options.