

COMPETENT FAST RELIABLE

ACR-M-1050 - Technical Specifications - Rental Chiller



Quick overview

Screw Compressor Refrigerant

Process Temperature

Sound Level









Optionally accessories

Cold Water Tubes Ext. Pump Module Heat Exchanger Electrical Cables Remote Monitoring











Different requirements and applications can be provided on request!

Technical specifications:

| *Cooling capacity | kW | 1053 |
|--|--------------------|---------------------------|
| Power input | kW | 349 |
| Voltage | V/Hz/Ph | 400/50/3 |
| Operating current | Α | 699 |
| Electrical connection | Cable terminals | 3 Ph + PE |
| ** Fuse protection | Α | on site |
| ** Cable recommendation | mm ² | 7 x 240 (Single wire) |
| Flow rate | m^3/h | 181,44 |
| Max. operating pressure | bar | 10 |
| | | |
| External pressure head | m | - |
| External pressure head Cold water connections | m Storz | 125 |
| • | *** | 125 12,5 - 100 |
| Cold water connections | Storz | |
| Cold water connections Capacity control | Storz % | 12,5 - 100 |
| Cold water connections Capacity control Refrigerant | Storz % - | 12,5 - 100 R134a |
| Cold water connections Capacity control Refrigerant Sound pressure at 5m | Storz % - dB(A) | 12,5 - 100 R134a 62 |

^{*} Design conditions: Evaporator water temperatures 12/7°, Ambient temperature 35 °C

Technical description:

Air cooled corrosion resistant chiller for outdoor locations. This mechanical refrigeration unit for providing cold water is equipped with very quiet running screw compressors. The fluid cooler should be set up on a horizontal, stable work area and have at least 2m free space to all sides. All controls and regulators are contained within the housing.

^{**} On-Site power installation should be entrusted to an electrical specialist.