

COMPETENT FAST RELIABLE

ACR-M-380/P - Technical Specifications - Rental Chiller



Quick overview

Screw Compressor Refrigerant

Process Temperature Integrated Pump Sound Level











Optionally accessories

Cold Water Tubes Heat Exchanger

Ext. Buffer Storage Electrical Cables Remote Monitoring











Different requirements and applications can be provided on request!

Technical specifications:

*Cooling capacity	kW	375
Power input	kW	121
Voltage	V/Hz/Ph	400/50/3
Operating current	Α	305
Electrical connection	Cable terminals	3 Ph + PE
** Fuse protection	Α	315
** Cable recommendation	mm ²	4 x 150 (Single wire)
Flow rate	m³ /h	64,3
Max. operating pressure	bar	10
Max. operating pressure External pressure head	bar m	10 24
External pressure head	m	24
External pressure head Cold water connections	m Storz	24 A
External pressure head Cold water connections Capacity control	m Storz	24 A 12,5 - 100
External pressure head Cold water connections Capacity control Refrigerant	m Storz %	24 A 12,5 - 100 R134a
External pressure head Cold water connections Capacity control Refrigerant Sound pressure at 5m	m Storz % - dB(A)	24 A 12,5 - 100 R134a 67

Design conditions: Evaporator water temperatures 12/7°, Ambient temperature 35 °C

Technical description:

Air cooled corrosion resistant chiller for outdoor locations. This mechanical refrigeration unit for providing cold water is equipped with a very quiet running screw compressor. The liquid cooler has an integrated cold water pump head height of 24m (240kPa), it should be set up on a horizontal, stable work area and have at least 2m free space to all sides. All controls and regulators are contained within the housing.

^{**} On-Site power installation should be entrusted to an electrical specialist.