

COMPETENT FAST RELIABLE

ACR-M-40/P - Technical Specifications - Rental Chiller



Ouick overview

Scroll Compressor Refrigerant

Frequency Drive

Integrated Pump

Sound Level











Optionally accessories

Cold Water Tubes Heat Exchanger

Ext. Buffer Storage

Electrical Cables Remote Monitoring











Different requirements and applications can be provided on request!

Technical specifications:

*Cooling capacity	kW	40
Power input	kW	14
Voltage	V/Hz/Ph	400/50/3
Operating current	Α	43
Electrical connection	Socket	CEE 63A
** Fuse protection	Α	50
** Cable recommendation	mm²	16
Flow rate	m³/h	3,9
Max. operating pressure	bar	6
External pressure head	m	37
External pressure head Cold water connections	m Storz	37 C
·	***	
Cold water connections	Storz	С
Cold water connections Capacity control	Storz	C 25-100 (FD)
Cold water connections Capacity control Refrigerant	Storz % -	C 25-100 (FD) R 32
Cold water connections Capacity control Refrigerant Sound pressure at 5m	Storz % - dB(A)	C 25-100 (FD) R 32 55

Design conditions: Evaporator water temperatures 12/7°, Ambient temperature 35 °C

Technical description:

Air cooled corrosion resistant chiller for outdoor locations. This mechanical refrigeration unit for providing cold water is equipped with very quiet running scroll compressors. The liquid cooler has an integrated cold water pump head height of 37m (370kPa), it should be set up on a horizontal, stable work area and have at least 1m free space to all sides. All controls and regulators are contained within the housing.

^{**} On-Site power installation should be entrusted to an electrical specialist.