




COMPETENT. FAST. RELIABLE

ACR-PUG-200 to 2000 - Technical Specifications - Closed buffer tank



Optionally accessories



Different requirements and applications can be provided on request!

Technical description:

Cold water buffer tank in closed design, upright, with nozzle pipe, made of sheet steel, unfinished inside, with insulation. The buffer tank is equipped with 4 connections, gate valve, sensor sleeves, drain and vent.

Technical specifications:

Buffer storage	L	200	500	1000	1500	2000
Medium temperature min./max.	°C	-10/+50	-10/+50	-10/+50	-10/+50	-10/+50
Max. operating pressure	bar	10	10	10	10	10
Connections	DN/Storz	С	В	100 / A	100 / A	125 / 125
No. of connections	No.	4	4	4	4	4
Weight	Kg	131	213	468	546	700
Dimensions (I x w x h)	mm	880x700x1710	1200x920x2000	1700x1030x2470	2040x1280x2470	2000x1400x2380

* Connections individually configurable on request

C acr chiller rent GmbH – Technical as well as structural changes may at any time be made without notice. The acr chiller rent GmbH terms and conditions apply.

acr chiller rent GmbH Otto-Perutz-Str. 8 81829 München Ph.: +49 (0)89 / 895 560 78-0 Fax: +49 (0)89 / 895 560 78-55 info@acr-rent.de **www.acr-rent.de**