



0800 / 12 24 100*

*Toll-free calls throughout Germany



COMPETENT. FAST. RELIABLE

ACR-SPOTCOOLER-7 – Technical Specifications – Portable Air-Conditioning Unit



Quick overview

Rotation
Compressor



Refrigerant



Cooling
Temperature



Ambient
Temperature



Integrated
Pump



Optionally accessories

Air Hose



Extension
Cable



Different requirements and applications can be provided on request!

Technical specifications:

*Cooling capacity	kW	7
Power input	kW	2,1
Voltage	V/Hz/Ph	230/50/1
Operating current	A	13
Electrical connection	Socket	230V
** Fuse protection	A	16
** Cable recommendation	mm ²	2,5
Control air flow volume	stage	1-2-3
Air flow volume	m ³ /h	800-1020
Refrigerant	R	1234YF
Sound pressure at 3 m	dB(A)	55
Condensate container	l	20
Weight	kg	85
Dimensions (l x w x h)	mm	500x620x1250

* Design conditions: Room temperature 26°C, 55% relative humidity, Ambient temperature 30°C

** On-Site power installation should be entrusted to an electrical specialist.

Technical description:

The ACR-SPOTCOOLER is a mobile air-conditioning unit that directs the cooled air through the flexible hoses to the area that requires temperature control. The unit is particularly suitable for spot cooling in production processes, server air conditioning, factory halls, etc. No specialist knowledge is required for installation. The unit fits through narrow doors and in lifts. Mobile cooling is available within a few minutes.