

COMPETENT, FAST, RELIABLE

ACR-EHW-9 to 36 – Technical Specifications – Rental electric water heaters



Ouick overview

Electric Air Heater Operating Range Integrated Pump Warm Water Hose Electrical Cables



Cto+85°C

Different requirements and applications can be provided on request!

Technical description:

Mobile acr electric heaters with a heat capacity up to 36 kW. The device is connected with a CEE connector and is immediately ready for use. Through the operation with three phase current, no exhaust fumes emerge and therefore the heater can be set up directly inside the building. The standard equipment includes all required components, such as recirculating pump, expansion container, safety fittings as well as a temperature regulator. The heater is preassembled and mounted on a hand cart which can be setup or dismantled by one person. For all scopes such as heat emergencies, reconstruction works, research and development, a mobile acr electric heater can be quickly and simply rented.

Technical specifications:

Heating capacity	kW	9	15	22	28	36
Capacity range	kW	4,2 to 8,4	7,2 to 14	14,4 to 21	21,6 to 28,8	30 to 36
*Electrical connection	-	16 A CEE	32 A CEE	32 A CEE	63 A CEE	63 A CEE
Degree of protection	-	IP 44/ F	IP 44/ F	IP 44/ F	IP 44/ F	IP 44/ F
Max. operating temperature	°C	85	85	85	85	85
Temperature range	°C	20-85	20-85	20-85	20-85	20-85
Tap water	-	Optional	Optional	Optional	Optional	Optional
Pump	-	Ja	Ja	Ja	Ja	Ja
Expansion tank	Liter	10	10	10	10	10
Safety valve heater	bar	3	3	3	3	3
Connection hoses	-	Geka-Plugs	Geka-Plugs	Geka-Plugs	Geka-Plugs	Geka-Plugs
Length	mm	600	600	600	600	600
Width	mm	560	560	560	560	560
Height	mm	1100	1100	1100	1100	1100
Weight (without water)	kg	60	60	60	60	60

^{*} On-Site power installation should be entrusted to an electrical specialist.