



0800 / 12 24 100\*

\*Toll-free calls throughout Germany



COMPETENT. FAST. RELIABLE

## ACR-M-100/P – Technical Specifications – Rental Chiller



### Quick overview

Scroll  
Compressor



Refrigerant



Process  
Temperature



Integrated  
Pump



Sound  
Level



### Optionally accessories

Cold Water  
Tubes



Heat  
Exchanger



Ext. Buffer  
Storage



Electrical  
Cables



Remote  
Monitoring



Different requirements and applications can be provided on request!

### Technical specifications:

<b>*Cooling capacity</b>	<b>kW</b>	<b>95</b>
Power input	kW	35
Voltage	V/Hz/Ph	400/50/3
Operating current	A	87
Electrical connection	Socket	CEE125 A
** Fuse protection	A	100
** Cable recommendation	mm <sup>2</sup>	5x35
Flow rate	m <sup>3</sup> /h	16,6
Max. operating pressure	bar	6
External pressure head	m	21
Cold water connections	Storz	B
Capacity control	Steps	2
Refrigerant	-	R410A
Sound pressure at 5m	dB(A)	58
Transport weight	kg	1200
Dimensions (l x w x h)	mm	2800x1420x2100

\* Design conditions: Evaporator water temperatures 12/7°, Ambient temperature 35 °C

\*\* On-Site power installation should be entrusted to an electrical specialist.

### Technical description:

Air cooled corrosion resistant chiller for outdoor locations. This mechanical refrigeration unit for providing cold water is equipped with very quiet running scroll compressors. The liquid cooler has an integrated cold water pump head height of 21 m (210 kPa), it should be set up on a horizontal, stable work area and have at least 1 m free space to all sides. All controls and regulators are contained within the housing.