



0800 / 12 24 100\*

\*Toll-free calls throughout Germany



COMPETENT. FAST. RELIABLE

## ACR-PM-5-40 – Technical Specifications – Pump Modul



### Technical specifications:

| Pump Capacity                   | kW                | 4,0           |
|---------------------------------|-------------------|---------------|
| Voltage / Electrical Connection | 400V/3/N/PE       | CEE16A Socket |
| Operating current               | A                 | 8,0           |
| Degree of protection            | Type              | IP 55         |
| Flow rate min / max             | m <sup>3</sup> /h | 5 / 45        |
| Pressure head min / max         | m                 | 14 / 28       |
| Max. operating pressure         | bar               | 10            |
| *Water connections              | Storz             | A             |
| Filter                          | Type              | KSB / DN 80   |
| Weight                          | kg                | 336           |
| Dimensions (l x w x h)          | mm                | 1660x680x1450 |

\* Connections individually configurable on request

### Optionally accessories

Cold Water Tubes



Heat Exchanger



Electrical Cables



Ext. Buffer Storage



Different requirements and applications can be provided on request!

### Technical description:

External pump module with CEE 16A plug, with high-pressure pump, frequency converter, switch cabinet, dirt trap, gate valve and fittings mounted on a stable base frame. Extensive accessories are available as options.

### Pump diagram:

