



0800 / 12 24 100\*

\*Toll-free calls throughout Germany



COMPETENT. FAST. RELIABLE

## ACR-SA-300-240-1 – Technical Specifications – Emergency Power Generator



### Optionally accessories

Electrical Cables



Ext. Tank



Distribution Box



Different requirements and applications can be provided on request!

### Technical specifications:

|                                     |            |                |
|-------------------------------------|------------|----------------|
| <b>Continuous Power</b>             | <b>kVA</b> | <b>300</b>     |
| Voltage                             | V/Hz/Ph    | 400/50/3       |
| Power factor                        | Cos phi    | 0,8            |
| Circuit breaker                     | A          | 400            |
| Fuel tank                           | l          | 270            |
| Fuel Consumption (100% prime power) | l/h        | 60             |
| Refuel period (permanent operation) | –          | 4,5            |
| Fuel                                | –          | Diesel         |
| Sound pressure at 5m                | dB(A)      | 70             |
| Weight                              | kg         | 5250           |
| Dimensions (l x w x h)              | mm         | 4170x1440x2380 |

### Technical description:

Emergency generator for outdoor installation in corrosion-resistant design. The unit has an integrated diesel tank, is designed as a covered unit and should be installed outdoors on a level, load-bearing surface. The default operating mode is isolated operation. Parallel mains operation, emergency power operation with built-in mains monitoring and back-synchronisation are also available as options.